

Geometrie		seat tube Sitzrohr	top tube Oberrohr	seat angle Sitzwinkel	head tube angle Lenkwinkel	head tube Steuerrohr	rear stays Hinterbau	seatpost Sattelstütze	travel Federweg	headset Steuersatz	Reach Reach	Stack Stack
<b>Tyke P1, 29"</b>	<b>S</b>	420mm	595	73°	69°	100	450	31,6		11/8"-1,5"	397	595
<b>Tyke ROSL, 29"</b>	<b>M</b>	470mm	612	73°	69°	120	450	31,6		11/8"-1,5"	413	611
	<b>L</b>	520mm	630	73°	69°	130	450	31,6		11/8"-1,5"	431	621
	<b>XL</b>	550mm	645	73°	69°	150	450	31,6		11/8"-1,5"	446	641
<b>Tyke SL, 27,5"</b>	<b>S</b>	430mm	585	73°	69°	120	435	31,6		11/8"-1,5"		
<b>Tyke P1, 27,5"</b>	<b>S/M</b>	450mm	590	73°	69°	120	435	31,6		11/8"-1,5"		
	<b>M</b>	480mm	600	73°	69°	120	435	31,6		11/8"-1,5"		
	<b>L</b>	530mm	625	73°	69°	130	435	31,6		11/8"-1,5"		
	<b>XL</b>	550mm	645	73°	69°	150	435	31,6		11/8"-1,5"		
<b>Tyke P1 AM 650 B+/29"</b>	<b>S</b>	423	595	74°	66°	110	440	31,6		11/8"-1,5"		
	<b>M</b>	450	620	74°	66°	120	440	31,6		11/8"-1,5"		
	<b>L</b>	480	630	74°	66°	130	440	31,6		11/8"-1,5"	430	668
	<b>XL</b>	520	645	74°	66°	150	440	31,6		11/8"-1,5"	445	681
<b>Tyke T1, 28"</b>		430mm	550	73°	69°	130	450	31,6		11/8"-1,5"		
<b>Tyke T1 Pinion, 28"</b>		480mm	565	73°	69°	140	450	31,6		11/8"-1,5"		
<b>Tyke T1 Rohloff, 28"</b>		520mm	574	73°	69°	150	450	31,6		11/8"-1,5"		
		540mm	580	73°	69°	160	450	31,6		11/8"-1,5"		
		560mm	585	73°	69°	170	450	31,6		11/8"-1,5"		
		580mm	600	73°	69°	170	450	31,6		11/8"-1,5"		
		610mm	615	73°	69°	190	450	31,6		11/8"-1,5"		
<b>Szenario, Pinion 650B /29"</b>	<b>S</b>	430	575	74°	67°	110	445	31,6	130-150	11/8"-1,5"		
	<b>M</b>	480	595	74°	67°	120	445	31,6	130-150	11/8"-1,5"		
	<b>L</b>	520	620	74°	67°	130	445	31,6	130-150	11/8"-1,5"		
	<b>XL</b>	550	635	74°	67°	150	445	31,6	130-150	11/8"-1,5"		
<b>Szenario E, Pinion 650B/ 29"</b>	<b>S</b>	430	575	74°	67°	120	455	31,6	130-150	11/8"-1,5"	438	621
<b>Gates, NeoDrives</b>	<b>M</b>	480	595	74°	67°	120	455	31,6	130-150	11/8"-1,5"	455	621
	<b>L</b>	520	620	74°	67°	130	455	31,6	130-150	11/8"-1,5"	470	630
	<b>XL</b>	550	635	74°	67°	150	455	31,6	130-150	11/8"-1,5"	482	650
<b>Fusion E MGU Herren</b>	<b>XS</b>	410	565	73°	69°	130	455-475	30,9		1,5"	370	625
<b>Herren, Trapez, Tiefeinstieg</b>	<b>S</b>	430	580	73°	69°	130	455-475	30,9		1,5"	384	633
	<b>M</b>	470	600	73°	69°	150	455-475	30,9		1,5"	404	633
<b>Fusion E, Neodrive</b>	<b>L</b>	520	626	73°	69°	150	455-475	30,9		1,5"	425	652
<b>Herren, Trapez</b>	<b>XL</b>	580	646	73°	69°	170	455-475	30,9		1,5"	445	665

Geometrie		seat tube Sitzrohr	top tube Oberrohr	seat angle Sitzwinkel	head tube angle Lenkwinkel	head tube Steuerrohr	rear stays Hinterbau	seatpost Sattelstütze	travel Federweg	headset Steuersatz	Reach Reach	Stack Stack
Zeno E 27,5"+/29" Pinion MGU Das Smarte System (GEN5) Gates, Bosch Rohloff, 3x3	S	440	590	73°	67°	120	465	30,9		1,5"	424	620
	S/M	450	605	73°	67°	120	465	30,9		1,5"	434	621
	M	480	625	73°	67°	120	465	30,9		1,5"	454	630
	L	520	635	73°	67°	130	465	30,9		1,5"	465	630
	XL	550	645	73°	67°	150	465	30,9		1,5"	476	640
	XXL	570	660	73°	67°	170	465	30,9		1,5"	489	645
Zeno E Trekking 28", Zeno E Das Smarte System (GEN5) Rohloff, Gates, Bosch Herren, Trapez, Tiefestieg	XS	410	550	73°	69°	130	465	30,9		1,5"		
	S	430	565	73°	69°	140	465	30,9		1,5"		
	M	480	574	73°	69°	150	465	30,9		1,5"		
	L	530	580	73°	69°	160	465	30,9		1,5"		
	XL	560	585	73°	69°	170	465	30,9		1,5"		
	XXL	580	600	73°	69°	170	465	30,9		1,5"		
Szenario E, Bosch und Pinion MGU 29", 27,5"+ Das Smarte System (GEN5) Gates, Bosch, Pinion MGU Rohloff, 3x3	S	420	600	74°	66°	120	468	30,9	140-160	1,5"	435	613
	M	450	615	74°	66°	130	468	30,9	140-160	1,5"	450	623
	L	500	625	74°	66°	130	468	30,9	140-160	1,5"	469	623
	XL	540	645	74°	66°	150	468	30,9	140-160	1,5"	479	635
	XXL	560	660	74°	66°	170	468	31,9	140-160	1,5"	490	640
Puna E 27,5"+/29" Carbon Das Smarte System GEN5 Bosch CX, Bosch Race	S	405	590	75°	66°	110	455	31,6	160	1,5"	432	619
	M	457	610	75°	66°	120	455	31,6	160	1,5"	441	630
	L	508	630	75°	66°	130	455	31,6	160	1,5"	461	638
Gravel Pinion Pinion C1,12, P1.12, P1.18 Gravel Rohloff, Rohloff Speedhub 500/14	XS	460	530	74°	70,5°	100	435-455	31,6		11/8"-1,5"	372	550
	S	490	545	73°	71°	120	435-455	31,6		11/8"-1,5"	381	560
	M	510	560	73°	71°	130	435-455	31,6		11/8"-1,5"	392	578
	L	530	585	73°	71°	150	435-455	31,6		11/8"-1,5"	403	595
	XL	560	600	73°	71°	170	435-455	31,6		11/8"-1,5"	415	609
E-Gravel SX Rohloff Rohloff Speedhub 500/14	XS	460	530	74°	70,5°	100	435-455	31,6		11/8"-1,5"	372	550
	S	490	545	73°	71°	120	435-455	31,6		11/8"-1,5"	381	560
	M	510	560	73°	71°	130	435-455	31,6		11/8"-1,5"	392	578
	L	530	585	73°	71°	150	435-455	31,6		11/8"-1,5"	403	595
	XL	560	600	73°	71°	170	435-455	31,6		11/8"-1,5"	415	609
Puna E 27,5"+/29" Carbon Das Smarte System Bosch SX	S	405	580	77°	66,5°	100	445	31,6	130	1,5"	440	607
	M	457	605	77°	66,5°	105	445	31,6	130	1,5"	464	611
	L	508	630	77°	66,5°	110	445	31,6	130	1,5"	487	616